



Envirotech Accent Blind Fabric

“Intelligent Blind Fabrics, Protecting You and The Environment.”

The weaving process of this flame retardant composition ensures the fabric has a distinguished and stylish look. Perfect for areas where privacy is needed with first-rate light shading and resistance to ignition.

With 22 colours and an ample range of fabric widths available, this fabric comes with a full Biosafe® accreditation which is the international accreditation standard of our proven antimicrobial formula that has been tested under the most stringent measures to ensure effective inhibiting of infection.



Accent Fire Retardant and Anti-Microbial

Presenting 22 colours and a convenient range of fabric widths available, this Flame Retardant and Biosafe® anti-microbial fabric is designed with the commercial, educational and healthcare environments in mind.

The perfect product for areas where privacy is needed as well as sufficient light shading. The potential applications for this fabric stretch the imagination.



| | |
|------------------------------|-------------------------------|
| Fabric Composition: | 100% Polyester |
| Fabric Range: | 22 |
| Louvre Widths: | 127mm (5") / 89mm (3.5") |
| Vertical Roll Length: | 100m |
| Roller Fabric Width: | 2000mm / 2500mm / 3000mm |
| Roller Fabric Length: | 30m / 20m |
| Fabric Thickness: | 0.3mm |
| Fabric Weight: | 220 g/m2 |
| Fire Retardancy: | BS5867, Part 2: Type B, 2008 |
| Shading: | Dimout |
| Moisture Resistance: | Suitable for moist conditions |
| Anti Bacterial: | Incorporates Biosafe® formula |



More fabric colours and
data tables overleaf...

Accent Fire Retardant and Anti-Microbial

| | 2500 / 3000 mm | 2000 mm | 127 mm | 89 mm | HT % | LT % | UP % | LA % | HR % | LR % | SC | GTOT |
|-----------|----------------|---------|--------|-------|------|------|------|------|------|------|------|------|
| Tan | | | | | 9 | 1 | 100 | 34 | 56 | 42 | 0.44 | 0.37 |
| Frost | | | | | 14 | 12 | 100 | 9 | 78 | 84 | 0.32 | 0.27 |
| Sesame | | | | | 13 | 12 | 100 | 10 | 77 | 82 | 0.32 | 0.28 |
| Vanilla | | | | | 13 | 10 | 90 | 13 | 73 | 77 | 0.35 | 0.29 |
| W. Almond | | | | | 23 | 8 | 90 | 16 | 71 | 73 | 0.35 | 0.30 |
| Sandstone | | | | | 13 | 9 | 100 | 16 | 71 | 74 | 0.36 | 0.30 |
| Linen | | | | | 12 | 7 | 100 | 18 | 70 | 71 | 0.36 | 0.30 |
| Cherry | | | | | 5 | <1 | 100 | 62 | 34 | 16 | 0.56 | 0.47 |
| Heather | | | | | 9 | 1 | 100 | 31 | 60 | 43 | 0.41 | 0.35 |
| Surf | | | | | 11 | 4 | 100 | 26 | 63 | 55 | 0.40 | 0.34 |
| Marine | | | | | 1 | <1 | 100 | 70 | 28 | 19 | 0.59 | 0.50 |
| Cobalt | | | | | 6 | 0 | 100 | 59 | 35 | 10 | 0.56 | 0.47 |
| D. Azure | | | | | 0 | 0 | 100 | 89 | 11 | 7 | 0.69 | 0.59 |
| Lawn | | | | | <1 | <1 | 100 | 80 | 20 | 19 | 0.64 | 0.54 |
| Apple | | | | | 4 | 1 | 100 | 54 | 42 | 42 | 0.52 | 0.44 |
| Mustard | | | | | 11 | 11 | 100 | 23 | 66 | 66 | 0.54 | 0.39 |
| Mist | | | | | 5 | 3 | 100 | 41 | 54 | 56 | 0.44 | 0.38 |
| Stone | | | | | 2 | 1 | 100 | 56 | 41 | 42 | 0.51 | 0.44 |
| Fossil | | | | | <1 | 10 | 100 | 23 | 27 | 28 | 0.71 | 0.61 |
| Graphite | | | | | <1 | 0 | 100 | 82 | 18 | 19 | 0.65 | 0.55 |
| Steel | | | | | 0 | 0 | 100 | 89 | 11 | 12 | 0.69 | 0.59 |
| Coal | | | | | 0 | 0 | 100 | 94 | 6 | 6 | 0.72 | 0.61 |

HT % : Heat Transmittance
LT % : Light Transmittance
UP % : Ultraviolet Protection
LA % : Light Absorption
HR % : Heat Reflection
LR % : Light Reflection
SC : Shading Co-Efficiency
GTOT : Total Value of Solar Energy

Tan

Frost

Sesame

Vanilla

W. Almond

Sandstone

Linen

Cherry

Heather

Surf

Marine

Cobalt

D. Azure

Lawn

Apple

Mustard

Mist

Stone

Fossil

Graphite

Steel

Coal